



DIMENSIONS & WEIGHTS

INSIDE DIAMETER	ASTM WALL	T	L	POUNDS PER FOOT	OD	A	B	C	D	E	F
15"	B	2.25"	8'	127	19.50"	2.00"	16.47"	16.97"	2.00"	16.97"	17.67"
18"	B	2.50"	8'	168	23.00"	2.00"	19.50"	20.00"	2.00"	20.00"	20.74"
24"	B	3.00"	8'	265	30.00"	3.00"	25.91"	26.41"	3.00"	26.41"	27.46"
30"	B	3.50"	8'	384	37.00"	3.75"	32.50"	33.06"	3.775"	33.06"	34.06"
36"	B	4.00"	8'	524	44.00"	3.75"	39.00"	39.56"	3.75"	39.56"	40.56"
42"	B	4.50"	8'	685	51.00"	3.25"	44.98"	45.73"	3.25"	45.73"	46.88"
48"	B	5.00"	8'	867	58.00"	3.75"	51.24"	51.99"	3.75"	51.99"	53.31"

General Notes

1. REINFORCED CONCRETE PIPE TO BE MANUFACTURED TO MEET THE FOLLOWING SPECS: ASTM-C76 (LATEST) ASHTO-M1.70 NCDOT/SCDOT
2. MORTAR OR FLEXIBLE PLASTIC TYPE JOINT TO MEET SPEC 88-8-210A & ASHTO M-1989
3. REINFORCED IN ACCORDANCE WITH APPLICABLE STANDARD BY WALL (B) & CLASS (II & IV)

MANHOLE CASTINGS
FRUIT PIPE
STEEL PIPE
GEOTEXTILE FABRICS
EROSION CONTROL



CATCH BASINS
CONCRETE PIPE
MANHOLE CASTINGS
CAST IRON GRATES & FRAMES

MID-ATLANTIC DRAINAGE, INC

1124 WHITE OAK LANE
GALLIWAY TERR., 306
(843) 356-4200

P. O. BOX 398
NC 28643
(843) 324-0888

**REINFORCED
CONCRETE
PIPE
TONGUE & GROOVE**

FILE NAME RCP001.DWG	Sheet
DATE 02.22.2010	1
DRAWN BY JSW	